

Коммерческие электрические плиты L700

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ote@nt-rt.ru || сайт: <https://lozamet.nt-rt.ru/>

L700.KEO2 COMMERCIAL ELECTRIC RANGE



Description

- 2-plate electric range (circular plates)
- dimensions: 400 x 700 x 270 mm
- power supply: 3 N ~400V 50Hz
- power rating: 5.2 kW

L700.KEO6 COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 1200 x 700 x 280 / 310 mm
- Dimensions with base: 1200 x 700 x 900 mm
- Round plates: Ø 220 mm
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Plate power: 6 x 2.6 kW = 15.6 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

KITCHEN BASES:

L700.P1200 – open base with shelf 1200 x 588 x 620 mm

L700.S1200 – open cabinet 1200 x 588 x 620 mm

L700.SD1200 – cabinet with doors 1200 x 633 x 620 mm with doors 400 x 633 x 620 mm

L700.KEO6 PET+SD COMMERCIAL ELECTRIC RANGE - LINE 700



Standard execution:

- Dimensions: 1200 x 700 x 900 mm
- **Round plates: Ø 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 40 A
- Kitchen power: 18.25 kW
- Plate power: 6 x 2.6 kW = 15.6 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 1/1:

- Power: 2.65 kW

- Continuous temperature control $50 \div 290\text{ }^{\circ}\text{C}$, on each set heating function:
 - bottom 1.5 kW + top 0.8 kW
 - bottom 1.5 kW
 - top 0.8 kW
 - grill 1.8 kW
 - grill 1.8 kW + convection
 - bottom 1.5 kW + top 0.8 kW + convection
 - back 2.6 kW + convection
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 560 x 370 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KE06 PE+SD COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 1200 x 700 x 900 mm
- **Round plates: Ø 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 40 A
- Kitchen power: 20.05 kW
- Plate power: $6 \times 2.6\text{ kW} = 15.6\text{ kW}$
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 2/1:

- Power: 4.45 kW
- Continuous temperature control $50 \div 290\text{ }^{\circ}\text{C}$, for each set heating function:
 - bottom 3.2 kW + top 1.2 kW
 - bottom 3.2 kW
 - top 1.2 kW
 - grill 2.75 kW
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 680 x 555 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KE2 COMMERCIAL ELECTRIC RANGE



Description

- 2-plate electric range (square plates)
- dimensions: 400 x 700 x 270 mm
- power supply: 3 N ~400V 50Hz
- power rating: 4.8 kW

L700.KE6 COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 1200 x 700 x 280 / 310 mm
- Dimensions with base: 1200 x 700 x 900 mm
- **Square plates: 220 x 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Plate power: 6 x 2.4 kW = 14.4 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

KITCHEN BASES:

L700.P1200 – open base with shelf 1200 x 588 x 620 mm

L700.S1200 – open cabinet 1200 x 588 x 620 mm

L700.SD1200 – cabinet with doors 1200 x 633 x 620 mm

L700.KEC2 COMMERCIAL ELECTRIC RANGE



Description

- 2 fields – 240 mm
- ceramic plate
- dimensions: 400 x 700 x 270 mm
- power supply: 3 N ~400V 50Hz
- power rating: 5.0 kW

L700.KE6 PET+SD COMMERCIAL ELECTRIC RANGE - LINE 700



Standard execution:

- Dimensions: 1200 x 700 x 900 mm
- **Square plates: 220 x 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 40 A
- Kitchen power: 17.05 kW
- Plate power: 6 x 2.4 kW = 14.4 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 1/1:

- Power: 2.65 kW
- Continuous temperature control 50 ÷ 290 °C, on each set heating function:
 - bottom 1.5 kW + top 0.8 kW
 - bottom 1.5 kW
 - top 0.8 kW
 - grill 1.8 kW
 - grill 1.8 kW + convection
 - bottom 1.5 kW + top 0.8 kW + convection
 - back 2.6 kW + convection
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 560 x 370 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KE6 PE+SD COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 1200 x 700 x 900 mm
- **Square plates: 220 x 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 40 A
- Kitchen power: 18.85 kW
- Plate power: 6 x 2.4 kW = 14.4 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 2/1:

- Power: 4.45 kW
- Continuous temperature control 50 ÷ 290 °C, for each set heating function:
 - bottom 3.2 kW + top 1.2 kW
 - bottom 3.2 kW
 - top 1.2 kW

- grill 2.75 kW
- fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 680 x 555 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KEC4 PET COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 800 x 700 x 900 mm
- Round cooking zones: Ø 240 mm
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Kitchen power: 12.65 kW
- Heating zone power: 4 x 2.5 kW = 10 kW
- Energy Dosage Regulator
- Plate overheating protection

Electric oven GN 1/1:

- Power: 2.65 kW
- Continuous temperature control 50 ÷ 290 °C, on each set heating function:
 - bottom 1.5 kW + top 0.8 kW
 - bottom 1.5 kW
 - top 0.8 kW
 - grill 1.8 kW
 - grill 1.8 kW + convection
 - bottom 1.5 kW + top 0.8 kW + convection
 - back 2.6 kW + convection
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 560 x 370 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KEO4 COMMERCIAL ELECTRIC RANGE



- 4-plate electric range (circular plates)
- dimensions: 700 x 700 x 270 mm
- power supply: 3 N ~400V 50Hz
- power rating: 10.4 kW

L700.KEO4 PET COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 800 x 700 x 900 mm
- **Round plates: Ø 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Kitchen power: 13.05 kW
- Plate power: 4 x 2.6 kW = 10.4 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 1/1:

- Power: 2.65 kW
- Continuous temperature control 50 ÷ 290 °C, on each set heating function:
 - bottom 1.5 kW + top 0.8 kW
 - bottom 1.5 kW
 - top 0.8 kW
 - grill 1.8 kW
 - grill 1.8 kW + convection
 - bottom 1.5 kW + top 0.8 kW + convection
 - back 2.6 kW + convection
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 560 x 370 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KEC4 COMMERCIAL ELECTRIC RANGE



- 4 stoves – 240 mm
- ceramic plate
- dimensions: 700 x 700 x 270 mm
- power supply: 3 N ~400V 50Hz
- power rating: 10.0 kW

L700.KEO4 PE COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 800 x 700 x 900 mm
- **Round plates: Ø 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Kitchen power: 14.85 kW
- Plate power: 4 x 2.6 kW = 10.4 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 2/1:

- Power: 4.45 kW
- Continuous temperature control 50 ÷ 290 °C, for each set heating function:
 - bottom 3.2 kW + top 1.2 kW
 - bottom 3.2 kW
 - top 1.2 kW
 - grill 2.75 kW
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 680 x 555 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KEO6 PE max COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 1200 x 700 x 900 mm
- **Round plates: Ø 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 40 A
- Kitchen power: 20.05 kW
- Plate power: 6 x 2.6 kW = 15.6 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven 3 x GN 1/1:

- Power: 6.65 kW
- Continuous temperature control 50 ÷ 290 °C, on each set heating function:
 - bottom 4.8 kW + top 1.8 kW
 - bottom 4.8 kW

- top 1.8 kW
- grill 4.0 kW
- Oven door with glass
- Oven lighting
- Oven chamber 1005 x 555 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KE4 COMMERCIAL ELECTRIC RANGE



Description

- 4-plate electric range (square plates)
- dimensions: 700 x 700 x 270 mm
- power supply: 3 N ~400V 50Hz
- power rating: 9.6 kW

L700.KE4 PET COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 800 x 700 x 900 mm
- **Square plates: 220 x 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Kitchen power: 12.25 kW
- Plate power: 4 x 2.4 kW = 9.6 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 1/1:

- Power: 2.65 kW
- Continuous temperature control 50 ÷ 290 °C, on each set heating function:
 - bottom 1.5 kW + top 0.8 kW
 - bottom 1.5 kW
 - top 0.8 kW
 - grill 1.8 kW
 - grill 1.8 kW + convection
 - bottom 1.5 kW + top 0.8 kW + convection
 - back 2.6 kW + convection
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting

- Oven chamber 560 x 370 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KE4 PE COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 800 x 700 x 900 mm
- **Square plates: 220 x 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Kitchen power: 14.05 kW
- Plate power: 4 x 2.4 kW = 9.6 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven GN 2/1:

- Power: 4.45 kW
- Continuous temperature control 50 ÷ 290 °C, for each set heating function:
 - bottom 3.2 kW + top 1.2 kW
 - bottom 3.2 kW
 - top 1.2 kW
 - grill 2.75 kW
 - fan operation without heating (defrosting)
- Oven door with glass
- Oven lighting
- Oven chamber 680 x 555 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KE6 PE max COMMERCIAL ELECTRIC RANGE



Standard execution:

- Dimensions: 1200 x 700 x 900 mm
- **Square plates: 220 x 220 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 40 A
- Kitchen power: 21.05 kW
- Kitchen power: 21.05 kW
- Cast iron plates, quick heating
- 6-step regulation of the heating power of the plate
- Protecting cooking plates from overheating

Electric oven 3 x GN 1/1:

- Power: 6.65 kW
- Continuous temperature control 50 ÷ 290 °C, on each set heating function:
 - bottom 4.8 kW + top 1.8 kW
 - bottom 4.8 kW
 - top 1.8 kW
 - grill 4.0 kW
- Oven door with glass
- Oven lighting
- Oven chamber 1005 x 555 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass

L700.KEC4 PE COMMERCIAL ELECTRIC RANGE**Standard execution:**

- Dimensions: 800 x 700 x 900 mm
- **Round cooking zones: Ø 240 mm**
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 25 A
- Kitchen power: 14.45 kW
- Heating zone power: 4 x 2.5 kW = 10 kW
- Energy Dosage Regulator
- Plate overheating protection

Electric oven GN 2/1:

- Power: 4.45 kW
- Continuous temperature control 50 ÷ 290 °C, on each set heating function:
 - bottom 3.2 kW + top 1.2 kW
 - bottom 3.2 kW
 - top 1.2 kW
 - grill 2.75 kW
- Oven door with glass
- Oven lighting
- Oven chamber 680 x 555 x 315 mm
- Three levels of guides
- Standard grate, trays on request

Execution options:

- Metal oven door without glass



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ote@nt-rt.ru || сайт: <https://lozamet.nt-rt.ru/>