

Коммерческие газовые плиты L900

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ote@nt-rt.ru || сайт: <https://lozamet.nt-rt.ru/>

L900.KG2 COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 450 x 900 x 280 / 310 mm
- Dimensions with base: 450 x 900 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: ~ 230 V, 50 Hz
- Burner power: 1 x 4.5 kW + 1 x 7.5 kW = 12 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption
- 7.5 kW double crown burner
- Cast iron cooking grates, ceramic enameled

Burner options:

- Version with 3 kW burner
- Burner configurations giving total kitchen power: 10.5 kW, 15 kW

Execution options:

- Without electrical power
- Pilot burner ignition: manual

KITCHEN BASES:

L900.P450 – open base with shelf 450 x 760 x 620 mm

L900.S450 – open cabinet 450 x 760 x 620 mm

L900.SD450 – cabinet with doors 450 x 805 x 620 mm

L900.KG6 COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 1350 x 900 x 280 / 310 mm
- Dimensions with base: 1350 x 700 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: ~ 230 V, 50 Hz
- Burner power: 2 x 4.5 kW + 2 x 7.5 kW + 2 x 9 kW = 42 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption

L900.KG4 COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 900 x 900 x 280 / 310 mm
- Dimensions with base: 900 x 900 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: ~ 230 V, 50 Hz
- Burner power: 1 x 4.5 kW + 1 x 7.5 kW + 2 x 9 kW = 30 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption
- 9 kW and 7.5 kW double crown burners
- Cast iron cooking grates, ceramic enameled

Burner options:

- Version with 3 kW burner
- Burner configurations giving total kitchen power: 25.5 kW, 33 kW

Execution options:

- Without electrical power
- Pilot burner ignition: manual

KITCHEN BASES:

L900.P900 – open base with shelf 900 x 760 x 620 mm

L900.S900 – open cabinet 900 x 760 x 620 mm

L900.SD900 – cabinet with doors 900 x 805 x 620 mm

L900.KG4 PG COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 900 x 900 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: ~ 230 V, 50 Hz
- Kitchen heat output: 36.8 kW
- Burner power: 1 x 4.5 kW + 1 x 7.5 kW + 2 x 9 kW = 30 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption

- 9 kW and 7.5 kW double crown burners
- Cast iron cooking grates, ceramic enameled

Burner options:

- Version with 3 kW burner
- Burner configurations giving total kitchen power: 40.5 kW, 43.5 kW

Execution options:

- Without electrical power
- Pilot burner ignition: manual

KITCHEN BASES:

L900.P1350 – open base with shelf 1350 x 760 x 620 mm

L900.S1350 – open cabinet 1350 x 760 x 620 mm

L900.SD1350 – cabinet with doors 1350 x 805 x 620 mm

- 9 kW, 7.5 kW double crown burners
- Cast iron cooking grates, ceramic enameled

Gas oven GN 2/1:

- Power: 6.8 kW
- „Continuous temperature control: 145 ÷ 290 °C
- Anti-leak protection
- „Pilot burner
- „Generator ignition
- „Oven door, plain, metal
- „Oven chamber 680 x 555 x 315 mm
- „Three levels of guides
- 'Standard rack, trays on request

Burner options:

- Version with 3 kW burner
- Burner configurations giving total kitchen power: 32.3 kW, 39.8 kW

Execution options:

- Without electrical power
- Pilot burner ignition: manual
- Oven ignition: piezoelectric
- Oven door with glass
- Oven lighting (power supply ~ 230 V, 50 Hz)

L900.KG6 PG+SD COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 1350 x 900 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: ~ 230 V, 50 Hz
- Kitchen heat output: 48.8 kW
- Burner power: 2 x 4.5 kW + 2 x 7.5 kW + 2 x 9 kW = 42 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption
- 9 kW, 7.5 kW double crown burners
- Cast iron cooking grates, ceramic enameled

Gas oven GN 2/1:

- Power: 6.8 kW
- „Continuous temperature control: 145 ÷ 290 °C
- Anti-leak protection
- „Pilot burner
- „Generator ignition
- „Oven door, plain, metal
- „Oven chamber 680 x 555 x 315 mm
- „Three levels of guides
- 'Standard rack, trays on request

Burner options:

- Version with 3 kW burner

L900.KG4 PET COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 900 x 900 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: ~ 230 V, 50 Hz
- Required installation fuse: 25 A
- Burner power: 1 x 4.5 kW + 1 x 7.5 kW + 2 x 9 kW = 30 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption
- 9 kW, 7.5 kW double crown burners
- Cast iron cooking grates, ceramic enameled

Electric oven GN 2/1:

- Power: 4.45 kW
- „Continuous temperature control 50 ÷ 290 °C, for each set heating function:
 - bottom 3.2 kW + top 1.2 kW
 - bottom 3.2 kW
 - top 1.2 kW
 - grill 2.75 kW
 - grill 2.75 kW + convection
 - bottom 3.2 kW + top 1.2 kW + convection
 - back 2.6 kW + convection
 - fan operation without heating (defrosting)
- „Oven door, plain, metal

- Burner configurations giving total kitchen power: 47.3 kW, 50.3 kW

Execution options:

- Without electrical power
- Pilot burner ignition: manual
- Oven ignition: piezoelectric
- Oven door with glass
- Oven lighting (power supply ~ 230 V, 50 Hz)

L900.KG6 PET+SD COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 1350 x 900 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: ~ 230 V, 50 Hz
- Required installation fuse: 25 A
- Burner power: 2 x 4.5 kW + 2 x 7.5 kW + 2 x 9 kW = 42 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption
- 9 kW, 7.5 kW double crown burners
- Cast iron cooking grates, ceramic enameled

Electric oven GN 2/1:

- Power: 4.45 kW
- „Continuous temperature control 50 ÷ 290 °C, for each set heating function:
 - bottom 3.2 kW + top 1.2 kW
 - bottom 3.2 kW
 - top 1.2 kW
 - grill 2.75 kW
 - grill 2.75 kW + convection
 - bottom 3.2 kW + top 1.2 kW + convection
 - back 2.6 kW + convection
 - fan operation without heating (defrosting)
- „Oven door, plain, metal
- „Oven chamber 680 x 555 x 315 mm
- „Three levels of guides
- 'Standard rack, trays on request

Burner options:

- „Version with 3 kW burner
- Burner configurations giving total kitchen power: 40.5 kW, 43.5 kW

- „Oven chamber 680 x 555 x 315 mm
- „Three levels of guides
- 'Standard rack, trays on request

Burner options:

- =Version with 3 kW burner
- Burner configurations giving total kitchen power: 25.5 kW, 33 kW

Execution options:

- Pilot burner ignition: manual
- Oven door with glass
- Oven lighting

L900.KG6 PE max COMMERCIAL GAS RANGE



Standard execution:

- Dimensions: 1350 x 900 x 900 mm
- Gas connection: R $\frac{1}{2}$ "
- Gazy: E, H, Lw, Ls, B/P, P
- Power supply: 3N ~ 400V, 50Hz
- Required installation fuse: 13 A
- Burner power: 2 x 4.5 kW + 2 x 7.5 kW + 2 x 9 kW = 42 kW
- Pilot burners
- Ignition: high voltage generator
- Anti-leak protection
- Saving flame 25% of gas consumption
- 9 kW, 7.5 kW double crown burners
- Cast iron cooking grates, ceramic enameled

Electric oven GN 2/1:

- Power: 6.65 kW
- „Continuous temperature control 50 ÷ 290 °C, for each set heating function:
 - bottom 4.8 kW + top 1.8 kW
 - bottom 4.8 kW
 - top 1.8 kW
 - grill 4.0 kW
- „Oven door, plain, metal
- „Oven chamber 1005 x 555 x 315 mm
- „Three levels of guides
- 'Standard rack, trays on request

Burner options:

- Version with 3 kW burner
- Burner configurations giving total kitchen power: 40.5 kW, 43.5 kW

Execution options:

- Pilot burner ignition: manual
- Oven door with glass
- Oven lighting



По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: ote@nt-rt.ru || сайт: <https://lozamet.nt-rt.ru/>